

Fluke VPS510-B ScopeMeter® Compact Probe



主な機能

- Ideal for small electronics applications
- Compact size designed for lower voltage applications
- Double insulated, 300 V CAT III rated
- 10:1 voltage ratio and 500 MHz bandwidth
- Available in red, blue, grey, and green

製品概要: Fluke VPS510-B ScopeMeter® Compact Probe

Use the Fluke VPS510-B (Blue) Compact Voltage Probe with the [Fluke 190 Series III](#) and Series II Portable Oscilloscopes or with the [MDA-500 Series Motor Drive Analyzers](#). These double insulated compact probes offer a 10:1 voltage ratio, and 500 MHz bandwidth making them ideal for small electronics applications. For industrial applications consider Fluke [VPS410-II-B Voltage Probes](#) or [VPS421 Series High Voltage Probes](#).

仕様: Fluke VPS510-B ScopeMeter® Compact Probe

Specifications*

Aenuation	10:1
-----------	------

Bandwidth	500 MHz
Max. input voltage	CAT III 300 V
Max. voltage to ground	CAT III 300 V
Input Resistance	10 MΩ
Input Capacitance	11.5 ± 1 pF
Compensation range	10...25 pF
Cable Length	1.2 m (3.9 ft)
Safety	IEC / EN 61010-031 UL 61010-031 CSA C22.2 No. 1010.2.031
Max. Altitude	2000 m
Pollution Degree	2
Protection Class	II (double insulation)

*Specification of probe is valid only when used with Fluke ScopeMeter 190-xxx models and MDA-500 series.

モデル



Fluke VPS510-B

ScopeMeter® Compact Probe for electrical applications

- (1) Blue voltage probe
- (1) Black hook clip for probe tip
- (1) Black ground lead with mini alligator clip
- (1) Ground spring for probe tip (CAT II 30 V max.)
- (1) Insulation sleeve for probe tip
- (1) BNC to probe tip adapter
- (1) Adjustment tool

Fluke. 動き続ける世界を支える

Fluke Corporation	
PO Box 9090, Everett, WA 98206 U.S.A./div>	
お問い合わせ先:	©2025 Fluke
フルーク	Corporation.
特約店営業部	仕様は、予告なく変更され
TEL : 03-6714-3114	る場合があります。
www.fluke.com/jp/	04/2025

世界で最も信頼されている
ツール