

Technische gegevens

55XXA/COIL 50 | 50-Turn Current Coil













MAX RATING:
30.2 A

⚠
WARNING: UNFUSED.
EXCEEDING ABOVE
RATINGS CAN CAUSE
BURN HAZARD OR
FIRE.

MAX DUTY CYCLE: $\pm 20A$, CONTINUOUS
$\pm 20A$, 50%
MAXIMUM ON TIME 5 MINUTES

FLUKE 375 FC

TRUE RMS CLAMP METER

ZERO \overline{A} Hz \overline{A} Hz \overline{A}

Hz \sim \overline{A}

+

Ω

mV \overline{V}

SAVE \overline{V}

OFF

LOG Peak MIN MAX Q Peak

COM \overline{V} Ω

CAT II 1000V
F CAT II 2000V







Productoverzicht: 55XXA/COIL 50 | 50-Turn Current Coil

Optional 50-turn current coil expands workload coverage for calibrating clamp meters and ammeters.

Includes an Accredited 17025 Calibration Certificate Traceable to International Standards with Data.

Specificaties: 55XXA/COIL 50 | 50-Turn Current Coil

Specifications	
Number of turns	50
Maximum current	20 A rms, continuous 30.2 A rms, 5 minutes
Maximum voltage, all inputs	30 V to Earth
Minimum inner diameter of clamp jaws	23 mm
Coil ratio	±0.65 %, 3 Hz to 440 Hz. Usable but unspecified at dc and above 440 Hz

Modellen



55XXA/COIL 50

50-Turn Current Coil

Includes an Accredited 17025 Calibration Certificate Traceable to International Standards with Data

Fluke. *Keeping your world up and running.®*

Fluke Belgium N.V.
Kortrijksesteenweg 1095
B9051 Gent
Belgium
Tel: +32 2402 2100
E-mail: cs.be@fluke.com
www.fluke.be

©2025 Fluke Corporation. Alle rechten
voorbehouden.

Wijzigingen zonder voorafgaande kennisgeving
voorbehouden.

04/2025

**Wijziging van dit document is niet toegestaan
zonder schriftelijke toestemming van Fluke
Corporation.**