

Technische gegevens

Fluke 700P06Ex Gauge Pressure



Belangrijkste kenmerken

- Rugged urethane molded case protects the module from rough handling and harsh conditions
- Features internal temperature compensation from 0 °C to 50 °C for full-accuracy performance
- Includes NIST-traceable calibration certificate
- Module can be calibrated locally using the Fluke 700PCK Pressure Calibration Kit, a PC, and a precision pressure source
- Certified by CSA: I.S. Class I, Div 1, Groups A-D T4, Ta = 0 °C to 50 °C
- ATEX II 1G EEx ia IIC T4 Compliant.
- One year warranty

Productoverzicht: Fluke 700P06Ex Gauge Pressure

Display pressure readings in any of 10 different pressure units you specify in the calibrator setup

Specificaties: Fluke 700P06Ex Gauge Pressure

Specifications

Range	100 psi / 690 kPa
-------	-------------------

Resolution	0.01 / 0.07
Reference Uncertainty (23 ± 3°C)	0.025%
Total ¹ Uncertainty 1 year	0.050
High Side Media ²	316 SS
Low Side Media ²	N/A
<p>1. Total uncertainty, one year for temperature range 0°C to +50°C. Total uncertainty, 1.0% of full span for temperature range -10°C to 0°C. Compensated temperature range is 15°C to 35°C.</p> <p>2. "Dry" indicates dry air or non-corrosive gas as compatible media. "316 SS" indicates media compatible with Type 316 Stainless Steel. "C276" indicates media compatible with Hastelloy C276.</p>	

Modellen



FLUKE-700P06EX

Fluke. *Keeping your world up and running.®*

Fluke Belgium N.V.
Kortrijksesteenweg 1095
B9051 Gent
Belgium
Tel: +32 2402 2100
E-mail: cs.be@fluke.com
www.fluke.be

©2025 Fluke Corporation. Alle rechten
voorbehouden.
Wijzigingen zonder voorafgaande kennisgeving
voorbehouden.
04/2025

**Wijziging van dit document is niet toegestaan
zonder schriftelijke toestemming van Fluke
Corporation.**