

## Probeset voor laagdoorlaatfilter (4 kHz)



### Productoverzicht: Probeset voor laagdoorlaatfilter (4 kHz)

One (blue) 10:1 probe for low frequency applications. Useful bandwidth is 4 kHz, reducing noise pick-up in noisy environments such as in automotive applications. The design is optimized for user's safety, double insulated according to IEC 1010-2-031 CAT III.

### Specificaties: Probeset voor laagdoorlaatfilter (4 kHz)

Specifications	
Probe length	2.5m (8 ft.)
Maximum signal voltage	600V rms. CAT III per IEC 1010-2-031
Maximum voltage to ground	600V rms. CAT III per IEC 1010-2-031
Aenuation	10x
Bandwidth	4 kHz
Input resistance	10 MΩ
Input capacitance	12.5pF
Compensation range	15 to 35 pF

When using the mini Test-hooks any potential must not exceed 42 Vpk / 30 Vrms

## Modellen



### Fluke PM8918 301

One (blue) 10:1 probe for low frequency applications. Useful bandwidth is 4 kHz, reducing noise pick-up in noisy environments such as in automotive applications. The design is optimized for user's safety, double insulated according to IEC 1010-2-031 CAT III.

---

**Fluke.** *Keeping your world up and running.®*

**Fluke Belgium N.V.**  
Kortrijksesteenweg 1095  
B9051 Gent  
Belgium  
Tel: +32 2402 2100  
E-mail: [cs.be@fluke.com](mailto:cs.be@fluke.com)  
[www.fluke.be](http://www.fluke.be)

©2025 Fluke Corporation. Alle rechten  
voorbehouden.

Wijzigingen zonder voorafgaande kennisgeving  
voorbehouden.

03/2025

**Wijziging van dit document is niet toegestaan  
zonder schriftelijke toestemming van Fluke  
Corporation.**