

Technische gegevens

9007 Portable Lab Dry-Well



Productoverzicht: 9007 Portable Lab Dry-Well

The 9007 covers -40 °C to 140 °C . No external cooling is needed, so you get -40 °C in normal ambient. Set-point accuracy is $\pm 0.15\text{ °C}$ and stability is better than $\pm 0.02\text{ °C}$.

This dry-well comes with a unique calibration at the full, six-inch depth of the well and at a three-inch depth for short probes. Coefficients for each calibration are stored in the dry-well and can be easily selected from the top-panel control buttons to match the length of the probe being tested.

Encased in an all-aluminum enclosure that is durable, waterproof, and meets the standards of MIL-T-28800, the 9007 comes with both RS-232 and IEEE-488 interface connections. A wide variety of inserts are available covering probe diameters from 1/16 inch (1.6 mm) to 5/8 inch (15.9 mm).

Specificaties: 9007 Portable Lab Dry-Well

Specifications	
Range	-40 °C to 140 °C at 25 °C
Accuracy	$\pm 0.15\text{ °C}$
Stability	$\pm 0.02\text{ °C}$

Heating Times	25 °C to 140 °C: 20 min.
Cooling Times	25 °C to -40 °C: 25 min.
Stabilization	10 minutes
Test Wells	19 mm dia. x 152 mm deep (3/4 x 6 in)
Communications	RS-232 and IEEE-488
Enclosure	Meets Type II, Class 3, Style D requirements of MIL-T-28800
Power	115 V ac (± 10 %), 5 A or 230 V ac (± 10 %), 2.4 A, switchable, 50/60 Hz, 560 W
Size (HxWxD)	35.1 x 27.4 x 42.9 cm (13.8 x 10.8 x 16.9 in)
Weight	16.3 kg (36 lb)
NIST-Traceable Calibration	Data at -40 °C, 0 °C, 25 °C, 75 °C, and 140 °C

Modellen



9007

Portable Lab Dry-Well, -40 °C to 140 °C, 1/4 in (6.36 mm) insert

Fluke. *Keeping your world up and running.®*

Fluke Nederland B.V.
Postbus 1337
5602 BH Eindhoven
Tel: +31 40 267 5100
E-mail: cs.nl@fluke.com
www.fluke.nl

©2025 Fluke Corporation. Alle rechten
voorbehouden.
Wijzigingen zonder voorafgaande kennisgeving
voorbehouden.
04/2025

**Wijziging van dit document is niet toegestaan
zonder schriftelijke toestemming van Fluke
Corporation.**