

Teknik veriler

## **HART DRYWELL CABLE | An interface cable kit that includes a null modem to connect the Fluke 754 with Fluke Calibration dry-wells and Micro-Baths to automate**



**Ürün İncelemesi: HART DRYWELL CABLE | An interface cable kit that includes a null modem to connect the Fluke 754 with Fluke Calibration dry-wells and Micro-Baths to automate**

Use the HART DRYWELL CABLE to connect the Fluke 754 with these Fluke Calibration temperature sources to automate and document the calibration of temperature sensors and transmitters in the field or at the bench.

- 6102, 7102, and 7103 Micro-Bath Thermometer Calibrators
- 9009 Industrial Dual-Block Thermometer Calibrator
- 9100S and 9102S Handheld Dry-Wells
- 9142, 9143 and 9144 Field Metrology Wells
- 9170, 9171, 9172 and 7173 Metrology Well Calibrators
- 9190A Ultra-Cool Metrology Well

In addition, for more advanced automation at the bench, MET TEMP II Temperature Calibration Software V5.0 is ideal for calibrations requiring multiple temperature sources, generating calibration coefficients and reports,

## Modeller



### **HART DRYWELL CABLE**

An interface cable kit that includes a null modem to connect the Fluke 754 with Fluke Calibration dry-wells and Micro-Baths to automate and document the calibration of temperature sensors and transmitters in the field or at the bench.

**Fluke.** *Keeping your world up and running.®*

**Fluke TURKIYE**

P.O. Box 1186  
5602 BD Eindhoven  
The Netherlands  
[www.fluke.com.tr](http://www.fluke.com.tr)

©2025 Fluke Corporation. All rights reserved.

Data subject to alteration without notice.

04/2025

**Mer information:**

U.S.A. (800) 443-5853 TR +31 (0)40 267 5100 Canada  
(905) 890-7600 Övrigt +1 (425) 446-5500

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**