

Tekni k veri ler

3160-3 | Comparison Insert, 2 holes at 3.2 mm (1/8 in), 2 at 4.76 mm (3/16 in), 2 at 6.35 mm (1/4 in), 2 at 9 mm (9/32 in), and 2 at 9.5 mm (3/8 in)





Modeller



3160-3

Comparison Insert, 2 holes at 3.2 mm (1/8 in), 2 at 4.76 mm (3/16 in), 2 at 6.35 mm (1/4 in), 2 at 9 mm (9/32 in), and 2 at 9.5 mm (3/8 in)

² Fluke Corporation 3160-3 | Comparison Insert, 2 holes at 3.2 mm (1/8 in), 2 at 4.76 mm (3/16 in), 2 at 6.35 mm (1/4 in), 2 at 9 mm (9/32 in), and 2 at 9.5 mm (3/8 in)



$\textbf{Fluke}. \ \textit{Keeping your world up and running}. \\ \textcircled{\$}$

Fluke TURKIYE

P.O. Box 1186
5602 BD Eindhoven
The Netherlands
www.fluke.com.tr
©2025 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
04/2025

Mer information:

U.S.A. (800) 443-5853 TR +31 (0)40 267 5100 Canada (905) 890-7600 Övrigt +1 (425) 446-5500

Modification of this document is not permitted without written permission from Fluke Corporation.

3 Fluke Corporation 3160-3 | Comparison Insert, 2 holes at 3.2 mm (1/8 in), 2 at 4.76 mm (3/16 in), 2 at 6.35 mm (1/4 in), 2 at 9 mm (9/32 in), and 2 at 9.5 mm (3/8 in)