

Teknik veriler

2627-S | Spare Sensor Kit with Standard-Accuracy Sensor





Ürün İncelemesi: 2627-S | Spare Sensor Kit with Standard-Accuracy Sensor

One of the potential advantages of a digital thermo-hygrometer is that instead of sending the entire unit out for calibration, you can simply swap sensors and send only the sensors due for calibration out of the lab. The 1620A “DewK” Thermo-Hygrometer allows you to swap sensors without shutting it down or discontinuing your other readings.

Smart sensors make this possible because all of the calibration information is contained inside the sensor. Your costs are reduced because the 1620A never needs to be calibrated since it is only a display. Spare sensors like the 2627-S are less expensive to store, ship and recalibrate than an extra chart recorder.

With each kit you get a:

- Standard-accuracy sensor
- Sensor wall mount bracket
- 7.6 m (25 ft) extension cable

Modeller



2627-S

Spare Sensor Kit with Standard-Accuracy Sensor

Fluke. *Keeping your world up and running.®*

Fluke TURKIYE
P.O. Box 1186
5602 BD Eindhoven
The Netherlands
www.fluke.com.tr

©2025 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
04/2025

Mer information:

U.S.A. (800) 443-5853 TR +31 (0)40 267 5100 Canada
(905) 890-7600 Övrigt +1 (425) 446-5500

**Modification of this document is not permitted
without written permission from Fluke Corporation.**