

**FLUKE®**

Teknik veriler

## PLS 5G Laser Level



## Temel özellikler

- Accuracy:  $\leq 1/8$  in at 30 ft. ( $\leq 3$  mm @ 10 m)
- Green laser beam
- Point laser direction: 90° up, down, left, right, forward
- Durable pendulum lock platform.
- IP54 rating to limit dust and water entry for years of operation on the job site.

## Ürün İncelemesi: PLS 5G Laser Level

The new PLS 5G green laser levels offer the durability and precision you expect from PLS, a Fluke Company. Our new laser level platform offers a pendulum lock platform for safe transport and tilt mode functionality. The fast settling, self-leveling pendulum gives you accurate point and reference lines almost instantly.

- The PLS 5G is a self-leveling, five-point green laser level (plumb, level, and square horizontal and vertical points) equipped for multiple applications.
- Includes the PLS Pendulum Target for easy transfer of points to the floor during square alignment.
- Kit includes floor stand and L-bracket for fast, easy overhang and centerline measurements.

## Özellikler: PLS 5G Laser Level

PLS 5G		
Baery	3 x AA Alkaline IEC LR6	
Baery Life, Continuous Use	Red	$\geq 30$ hours
	Green	$\geq 9$ hours
Point Laser Direction	90° up, down, left, right, forward	
Working Range	$\leq 30$ m (100 ft.)	
Accuracy	$\leq 3$ mm @ 10 m ( $\leq 1/8$ in at 30 ft.)	
Laser Leveling	System	Automatic, Pendulum
	Range	4 °
Point Laser Diameter	$\leq 4$ mm at 5 m	
Temperature	Operating	-10 °C to 50 °C (14 °F to 122 °F)
	Storage	15 cm x 9 cm x 3 cm (6 in x 3.6 in x 1.3 in)
	With Baeries	-18 °C to 50 °C (-0.4 °F to 122 °F)
	Without Baeries	-20 °C to 70 °C (-13 °F to 158 °F)
Relative Humidity	0 % to 90 % (0 °C to 35 °C)	
	0 % to 75 % (35 °C to 40 °C)	
	0 % to 45 % (40 °C to 50 °C)	
Size (H x W x L)	116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in)	
Weight	~0.6 kg (1.3 lb.)	



**PLS 5G**

<b>Safety</b>	IEC 61010-1: Pollution Degree 2	
<b>Laser</b>	IEC 60825-1:2014 Class 2	
<b>Light Source</b>	Semiconductor laser diode	
<b>Max Output Power</b>	< 1 mW	
<b>Wavelength</b>	Red	635 nm ± 5 nm
	Green	525 nm ± 5 nm

**Electromagnetic Compatibility (EMC)**

Inteational  
Korea (KCC)  
USA (FCC)

**Fluke.** *Keeping your world up and running.®*

**Fluke TURKIYE**  
P.O. Box 1186  
5602 BD Eindhoven  
The Netherlands  
www.fluke.com.tr

©2025 Fluke Corporation. All rights reserved.  
Data subject to alteration without notice.  
04/2025

**Mer information:**

U.S.A. (800) 443-5853 TR +31 (0)40 267 5100 Canada  
(905) 890-7600 Övrigt +1 (425) 446-5500

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**