

Thông số kỹ thuật

Fluke PM9082 Dual Banana Jack (female) to male BNC Adapter



Tính năng chính

- Maximum Signal Voltage: 600V rms
- Maximum Voltage to Ground: 600V rms. CAT III per IEC 61010-031

Tổng quan sản phẩm: Fluke PM9082 Dual Banana Jack (female) to male BNC Adapter

The set consists of two adapters. One red (signal) and one black (ground) 4-mm banana contact.

Model



Fluke PM9082

Fluke PM9082 Dual Banana Jack (female) to male BNC Adapter

Fluke. *Giữ cho thế giới của bạn. không ngừng vận động.*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Europe/M-East/Africa
+31 (0)40 267 5100
In Canada (905) 890-7600
From other countries +1 (425) 446-5500

Representative office of Fluke South East Asia Pte Ltd

C/O Danaher Vietnam
Green Power Tower, 11th Floor Unit 2
35 Ton Duch Thang Street, District 1
Ho Chi Minh City
Vietnam
Tel: +84-8-2220-5371 (ext 103)
Email: info.asean@fluke.com
www.fluke.com/vn

©2025 Fluke Corporation. Specifications subject to change without notice.
04/2025

Modification of this document is not permitted without written permission from Fluke Corporation.