

Thông số kỹ thuật

Fluke BC7217 Battery Charger



Tổng quan sản phẩm: Fluke BC7217 Battery Charger

Description: Battery charger UL, CSA, MITI, DEMKO, FINKO, SEMKO recognized. CE compliant. EMI per FCC part 15 Class B.

Application: Select 120 volt version for use in North America. Select INTL version for use outside of North America. Line voltage 100 to 250V ac, frequency 50 to 60 Hz. IEC 320 inlet, line cord will be provided based on country of destination.

Included: Battery charger base, power supply (plus line cord for INTL version).

Dimensions: Power supply: 3.9" x 2.6" x 1.6" (100 mm x 66 mm x 41 mm); 72" (1.8m) cord
Charger base: 4.6" x 4.1" x 2.7" (116 mm x 104 mm x 58 mm)

Weight: 1.7 lb/0.78 kg

Warranty: One year

Thông số kỹ thuật: Fluke BC7217 Battery Charger

Specifications

Dimensions	Power supply	3.9 x 2.6 x 1.6 in (100 x 66 x 41 mm); 72 in (1.8 m) cord
	Charge base	4.6 x 4.1 x 2.7 in (116 x 104 x 58 mm)
Weight	1.7 lb / 0.78 kg	
Warranty	One year	

Model



Fluke BC7217

Battery Charger

Included:

- Battery charger base
 - Power supply (plus line cord for INTL version).
-

Fluke. *Giữ cho thế giới của bạn. không ngừng vận động.*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

Representative office of Fluke South East Asia Pte Ltd

C/O Danaher Vietnam
Green Power Tower, 11th Floor Unit 2
35 Ton Duch Thang Street, District 1
Ho Chi Minh City
Vietnam

Tel: +84-8-2220-5371 (ext 103)

Email: info.asean@fluke.com

www.fluke.com/vn

©2025 Fluke Corporation. Specifications subject to change without notice.
04/2025

For more information call:

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (905) 890-7600

From other countries +1 (425) 446-5500

Modification of this document is not permitted without written permission from Fluke Corporation.