

技術資料

AC288 Terminal Block Probe with Retractable Probe Tip





主要功能

- Retractable probe tip designed for increased safety, while providing flexibility to reach deep connection points
- Recommended for use with TL224, TL222 or TL221 Test Leads
- 11.5 cm (4.5 in) insulated, flexible shaft
- 1 mm diameter probe tip extends out to 8.4 mm (0.33 in) length
- Retractable probe tip is made with stainless steel
- Safety rated: IEC 61010-031, CAT III 1000 V, CAT IV 600 V
- Operating temperature: -20 °C to 55 °C (-4 °F to 131 °F), 90% RH
- One-year warranty

產品概述: AC288 Terminal Block Probe with Retractable Probe Tip

Use for safe and secure connections to clamp and screw type terminal blocks.

機型



AC288

Fluke. 保持您的世界運作不懈。

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

更多資訊
U.S.A. (800) 443-5853
Europe/M-East/Africa
+31 (0)40 267 5100
Canada (800)-36-FLUKE
其他 +1 (425) 446-5500
www.fluke.com/zh-tw

©2025 Fluke Corporation. Specifications subject to
change without notice.
04/2025

Modification of this document is not permitted
without written permission from Fluke Corporation.