

# Fluke TP175 TwistGuard Test Probes



## 主要功能

- Patented TwistGuard™ extendable tip shroud ensures electrical safety by reducing tip exposure while preserving versatility for different measurements
- Known for superior quality, ensuring reliable and accurate testing in industrial environments
- Rated CAT II 1000 V, CAT III 1000 V, CAT IV 600 V
- see compatible products below

## 產品概述: Fluke TP175 TwistGuard Test Probes

- Adjustable tip length, allowing increased safety and precision
- Compatible with the TL22x series, TL238 and TL27 test leads
- Conforms to EN61010-031
- CAT II 1000 V, CAT III 1000 V, CAT IV 600, 10 A rating, CSA Listing
- One-year warranty

## 規格: Fluke TP175 TwistGuard Test Probes

Specifications	
Ratings	CAT II 1000 V, CAT III 1000 V, CAT IV 600 V, 10 A max., Pollution Degree 2
Exposed probe tip length	19 mm to 4 mm (0.75 inch to 0.16 inch)

Environmental ratings	-20°C to 55°C (-4°F to 131°F) altitude: 2000 m (6,562 ft)
TL175 and TL175E also available. TL175E includes removable 4 mm lanse tips that thread onto the lead tip.	
Conforms to EN61010-031	

## 機型



Fluke TP175

TwistGuard™ Test Probes

---

Fluke. 保持您的世界運作不懈。

Fluke Corporation  
PO Box 9090, Everett, WA 98206 U.S.A.

更多資訊  
U.S.A. (800) 443-5853  
Europe/M-East/Africa  
+31 (0)40 267 5100  
Canada (800)-36-FLUKE  
其他 +1 (425) 446-5500  
[www.fluke.com/zh-tw](http://www.fluke.com/zh-tw)

©2025 Fluke Corporation. Specifications subject to  
change without notice.  
04/2025

Modification of this document is not permitted  
without written permission from Fluke Corporation.