


# 6003A Three Phase Electrical Power Calibrator







## 產品概述: 6003A Three Phase Electrical Power Calibrator

### Accurate performance for the calibration laboratory

Until now, many engineers and technicians have been testing three-phase devices with a single-phase series-parallel technique, because the cost of available three-phase sources with acceptable accuracies has put true polyphase testing out of reach. With the 6003A, these professionals can now afford three-phase performance, accuracy, and ease of use. More importantly, they can now test multi-phase meters in conditions that reflect their actual usage.

Along with providing three independent phases of precise voltage and current, the 6003A also sources power quality phenomena, including harmonics, interharmonics, flicker (modulation) and dip/swell variations.

The 6003A includes measurement capabilities for dc voltage, dc current and frequency for measuring outputs from power and energy transducers.

As a single instrument, the 6003A is easier to transport and takes up less space on the bench or cart than multi-piece units. The 6003A delivers all of this functionality with a graphical user interface that makes it remarkably easy to learn and use.

### Versatile and convenient functionality for the manufacturing floor

The 6003A is a single-instrument solution for single or multi-phase sourcing applications, making it ideal for many applications within electronics manufacturing companies and electric utility meter shops.

Now you can efficiently conduct final verification of power transducers, current transformers, energy meters, and revenue meters using true multi-phase testing methods. Test and calibrate single and multi-phase power meters, power quality analyzers and energy meters.

Put the 6003A on a cart and wheel it easily around the factory floor to test workload in situ. The graphical user interface makes setup a snap; all three phases are readily available for verification testing.

### Add capabilities with options and accessories

The energy option adds an energy pulse counter and pulse output to the 6003A to calibrate and test energy measurement devices. With this option, you can use the 6003A as the energy reference standard. Generated energy is compared with the pulses received from the unit under test (UUT) and a percentage error is reported for the UUT being tested. The generated energy can be expressed as a set amount (packet or dose mode), or for a given amount of pulses or time, along with a user determined warm-up period (timer and counter modes). It also has a free run mode for troubleshooting setups. A “Maintain Voltage Signal” feature provides power continuously to the UUT during different test sequences, useful when testing energy meters that take power from the voltage source.

The power quality option enables the 6003A to calibrate power quality instrumentation by generating a variety of power output phenomena on any or all of the voltage and current outputs. The types of phenomena include up to 63 simultaneous harmonics, a single interharmonic, apply modulation (flicker) and impose dips and swells on any or all of the six outputs of the three channels.

The 90 A adapter and high current leads accessory allows you to conveniently generate up to 90 A from a single

current phase, which can help you handle your high current workload. You can also use Fluke Calibration coil accessories to support testing of current clamps making measurements up to 4,500 A. The Fluke Calibration 52120A Transconductance Amplifier can provide additional boosted current phases up to 120 A ac per phase. Multiple 52120As can be used to increase current on multiple phases.

## Automate to increase throughput and efficiency

Quality standards impose stringent requirements for documenting, reporting, and controlling calibration processes and results. The GPIB and USB interfaces permit such automated control of the testing process. Users can create their custom programs to do unique and special tests. Using off-the-shelf commercial products, such as MET/CAL® *Plus* Calibration Management Software, can help you meet these requirements easily while also enabling you to increase throughput and streamline your meter calibration processes.

The MET/CAL *Plus* application is a powerful tool for creating, editing and testing calibration procedures and collecting and reporting results on a wide variety of instruments. It includes MET/CAL® software– the industry-leading software for automated calibration and MET/TEAM® software– a flexible system to manage your test and measurement assets. It is the most complete software solution available to calibration professionals.

## Priority software support helps you stay productive

MET/SUPPORT<sup>SM</sup> Gold is an annual membership program offering premium support and services to help you stay as productive as possible with MET/CAL Calibration Management Software. Services include free software updates and upgrades, free access to the MET/CAL Warranted Procedures Library, plus discounts on training and custom procedure development. Members also receive invitations to regular calibration software web seminars and user group meetings. Use only a few of the Gold services and you can easily recover more than the cost of your membership fee.

## Metrology training increases skill levels

Calibration and metrology training from Fluke Calibration can help you and your staff become more knowledgeable in a wide variety of disciplines. Instructor-led classroom training is available for general topics in metrology, as well as for calibration software. On-site training can also be scheduled if you have a number of people in your organization who would benefit.

Fluke Calibration also offers other educational events such as web seminars and road shows on a wide variety of topics. The best way to stay informed about these events is to register to receive email and direct mail from Fluke Calibration. You can register online at [subscribe to e-news bulletins](#), web seminar invitations, and more.

## Calibration and repair service

Fluke Calibration offers extensive calibration support and service to ensure your long-term satisfaction and return on investment in resistance calibrators, dc calibrators, current calibrators, voltage calibrators, and other calibration equipment. Our worldwide network of calibration centers offers accredited calibrations traceable to national standards. We also offer fast, quality repair and calibration services including a module exchange program and full support in setting up your lab.

## 規格: 6003A Three Phase Electrical Power Calibrator

Summary of Standard Capabilities			
AC power	0.008 VA to 18 kVA (each channel); 1, 2 or 3 channels		
Fundamental ac frequency range	15 Hz to 1 k Hz		
DC power	0.008 VA to 18 kVA (1 channel)		
AC voltage	AC to 600 V, 3 channels		
DC voltage	1 to 280 V		
AC current	0.008 to 30 A, 3 channels		
DC current	0.008 to 30 A		
High current	up to 90 A max, dc or ac, 1 channel		
Voltage from current terminals	DC and sine wave only		
	1 mV to 5 V		
	AC 15 Hz to 400 Hz		
Multimeter capabilities	Voltage – dc voltage up to $\pm$ 12 V		
	Current – dc current up to $\pm$ 25 mA		
	Frequency – up to 15 kHz		
Interfaces	GPIB and USB		
Optional power quality functions	Harmonics		
	Interharmonics		
	Flicker modulation		
	Dip/swell		
Optional electrical energy	Pulse input to 1 MHz		
	Energy pulse output		
	Trigger, synchronization input		
	Test duration up to 1,000 hours		
Key Performance Details			
Output parameter	Output Range	Best 1 Year Spec	Other
AC voltage per phase	1 V to 600 V	0.012%	300 mA max burden
AC current per phase	0.008 A to 30 A	0.0175%	5.5 V max compliance
Fundamental frequency range	15 Hz to 1 KHz	0.005%	
High current range (dc or ac)	90 mA to 90 A	0.0245%	5 V max compliance
DC voltage	1 V to 280 V	0.015%	200 mA max burden
DC current	0 to 30 A	0.0175%	8 V peak compliance
Voltage from current terminals	1mV to 5V	0.05%	15 Hz to 400 Hz

Phase range		0.0 to 359.99 °	0.01 °	0.01 ° resolution
Power factor range		-1 to +1 (lead, lag)		0.001 resolution
Selected Power Specifications				
Sinusiodal AC Power				
3 phases, PF 1	150 W, 10 V, 5 A, 40-75 Hz		0.037%	
3 phases, PF 0.8	120 W, 10 V, 5 A, 40-75 Hz		0.045%	
3 phases, PF 0.5	75 W, 10 V, 5 A, 40-75 Hz		0.071%	
DC Power				
Single phase	50 W, 10 V, 5 A		0.038%	
Multimeter Capabilities				
DC voltage	0 V to ± 12 V		0.01%	
DC current	0 mA to ± 25 mAV		0.01%	
Frequency	1 Hz to 15 kHz		0.005%	
Energy Option				
Pulse input	1 MHz max frequency			
	500 ns min pulse width			
	5 x 10 <sup>9</sup> max counts			
Pulse output	0.02 Hz to 1 MHz		1 to 1 x 10 <sup>8</sup> seconds	
	Time range			
Time resolution	0.1 seconds			
Time interval spec	0.01%			
Test duration	1,000 hours			
Power Quality Option				
Voltage and Current Modulation (Flicker)				
Modulation depth		0 to 30 %		
Modulation depth specification		0.2 % of modulation depth		
Modulation depth seing resolution		0.001%		
Shape of modulation envelope		Rectangular or siunusoidal		
Duty cycle for rectangular modulation		1 % to 99 %		
Modulating frequency specification		50 ppm of output		
Modulation frequency range		0.001 Hz to 50 Hz		
RMS amplitude specifiration		0.2% of range		
Fundamental frequency range		15 Hz to 1 kHz		
Harmonics and Interharmonics				
Applicable outputs		Voltage and/or current, all channels		

Fundamental frequency range	15 Hz to 1 k Hz
Amplitude specification	0.20%
Harmonic frequency range	30 Hz to 5 kHz
Maximum number of voltage harmonics	63 including the 1st (fundamental frequency), per output, up to 3 outputs
Maximum number of current harmonics	63 including the 1st (fundamental frequency), per output, up to 3 outputs
Interharmonic frequency range	15 Hz to 1 KHz
Number of independent interharmonic products	1 per output, up to 6 outputs
Maximum amplitude of harmonics	30% of RMS output value
Harmonic (2 to 63) phase specification	5 $\mu$ s
Dip/swell	
AC voltage range	0.1 to 280 V
AC current range	1 mA to 30 A
Amplitude accuracy	0.20%
Frequency range	15 Hz to 1 kHz
Timing	
Trigger to start of dip/swell	0 to 60 s
Dip/swell starting transition	0.1 ms to 60 s
Dip/swell time	2 ms to 60 s
Dip/swell ending transition	0.1 ms to 60 s
Stable time following dip/swell	0 to 60 s
General Specifications	
Input Power	
Voltage	Selectable 115 V or 230 V, $\pm$ 10%
Frequency	47 Hz to 63 Hz
Maximum consumption	1875 VA max
Dimensions	
Height	415 mm (61.3 in)
Height (without feet)	402 mm (15.8 in)
Width	430 mm (16.9 in)
Depth	640 mm (25.2 in)
Weight	62 kg (136 lb)
Environment	
Operating temperature	5 °C to 40 °C
Calibration temperature (Tcal) range	21 °C to 25 °C

Storage temperature	-10 °C to 55 °C
Transit temperature	-15 °C to 60 °C
Warm up time	1 hour
Safe operating max. relative humidity (non-condensing)	<80 % 5 °C to 31 °C ramping linearly down to 50 % at 35 °C
Storage max. relative humidity (non-condensing)	<90%, -10 °C to 55 °C
Operating altitude	2,000 m max
Storage altitude	12,000 m max
Shock	MIL-PRF-2880F class 3
Vibration	MIL-PRF-2880F class 3
Enclosure	MIL-PRF-2880F class 3



## 機型



6003A  
Three Phase Power Calibrator

---

6003A/E  
Three Phase Power Calibrator with Energy Option

---

6003A/PQ  
Three Phase Power Calibrator with Power Quality Option

---

6003A/PQ/E  
Three Phase Power Calibrator with Power Quality and Energy Options

---

Fluke. 保持您的世界運作不懈。

Fluke Corporation  
PO Box 9090, Everett, WA 98206 U.S.A.

更多資訊  
U.S.A. (800) 443-5853  
Europe/M-East/Africa  
+31 (0)40 267 5100  
Canada (800)-36-FLUKE  
其他 +1 (425) 446-5500  
[www.fluke.com/zh-tw](http://www.fluke.com/zh-tw)

©2025 Fluke Corporation. Specifications subject to  
change without notice.  
04/2025

Modification of this document is not permitted  
without written permission from Fluke Corporation.